

awi BP-9000E



24-PIN

Business Advantage

Heavy - Duty and High speed Printing in Graphic Mode!

- High speed
awi BP-9000E 846cps (SSD mode, 15cpi)
- 7 resident LQ fonts
- 1+8 multipart forms capability
- 2 emulation modes: EPSON ESC/P2 IBM 2391
- 132Kbyte data buffer
- Interface : Centronics (IEEE 1284 NIBBLE), RS-232C
USB (USB2.0 Full-speed) 10/100 Base-T Ethernet

Bar Code



auí BP-9000E

24-pin wide-carriage dot matrix printer

Specifications

	auí BP-9000E
Print method	24-pin dot matrix impact/bidirectional (text & graphics)
Print speed	Super Speed Draft : 864cps (15cpi) Speed Draft (12cpi) : 676cps Drft pica (10cpi) : 564cps HQR Pica (10cpi) : 360cps NLQ Pica (10cpi) : 240cps LQ Pica (10cpi) : 180cps
Graphic print speed	10.5 ips, or 18.0 ips or 24.0 ips (180/360DPI) 15.7 ips, or 18.0 ips or 31.5 ips (120/240DPI)
Line feed speed	60 or 30 lines/second (6 lines/inch) selectable
Line feed pitch	1/360"
Emulation	EPSON ESC/P2, IBM 2391
Data buffer	132 Kbytes
Resident fonts	Roman, Sans-serif, Courier, Prestige, Script, OCR-A, OCR-B,
Characters	Epson character sets, IBM code pages,
Attributes	Italic, condensedbold,double-strike, double-width,double-height, superscript, subscript, overscore, underscore
Paper feed	Push tractor or friction
Paper path	Rear (frankfold) or top (cut sheet)
Paper weight	53 to 105 g/m ² (14 to 28 lbs) Cut sheet : 64 to 105 g/m ² (17 $\frac{1}{2}$ to 28 lbs.)
Paper width	5" to 16" (frankfold & cut sheet)
Multipart forms	Original plus 8 duplicates
Ribbon	Special cassette-type black fabric ribbon (#BP-9000)
Download	Epson : 128 download characters IBM : 32 Kbytes
Interface	Centronics(parallel IEEE1284 nibble), RS-232C(serial) USB(USB2.0 Full-speed), 10/100 Base-T Ethernet
Printhead life	500 million dots / pin(MCBF)
Ribbon life	20 million characters (#BP-9000)
Powersupply	AC 100-240V 50/60 Hz
Power consumption	210 watts (maximum) 2 watts (sleep mode)
Dimonsions (W x D x H)	620 x305x280mm (24.4" x12.0" x10.2") 620 x455x295mm (24.4" x17.9" x11.6" in) with paper rack and sound seal cover
Weight	Approx. 20 kg(44.1 bs)
Epson® is a registered trademark of S.Epson Corporation. IBM® is a registered trademark of International Business Machines Corporation.	

These specifications are subject to change without notice.

*1 Planning

Take the Initiative - Choose the auí BP - 9000E

Leadership in business demands certain qualities - proficiency, alacrity, and absolute professionalism.

Such are the characteristics that AUI BP-9000E printing, have to offer with its movable printhead, 2 emulations, bar code, 1+8 multipart forms capability, 7 resident LQ fonts, and 132 Kbyte data buffer.

At speeds of up to 846 cps (Super Speed Draft mode), it can handle even the most daunting print jobs without holding up the rest of your work.

AUI BP-9000E is also equipped with a Zoom function which quickly and easily change the size of the printed characters to 50%~100%. *1 Most importantly however, the technical excellence is balanced by it's superb operating ease. For any and all business needs, choose AUI BP-9000E - the printer that means business.

Bar code printing

The AUI BP-9000E is also an ideal choice for bar code printing. The widespread adoption of these codes has led to significant increases in efficiency and accuracy, but high-quality printing is essential. All major types of bar code can be output by AUI BP-9000E with speed and clarity : Industrial 2 of 5, Inderleaved 2 of 5, Code 39, Code 128B, Code 128C, EAN-8, EAN-13 and NW-7.

2-level menu system

Operation is refreshingly simple, thanks to the innovative 2-level menu system(no DIP switches) which displays selections on LCD panel English. The AUI BP-9000E even stores 3 complete configurations for instant recall and provides detailed error messages.

Enhanced Interfaces

AUI BP-9000E is reequipped with Parallel, Serial, USB and LAN interfaces.

Flexible customization at request

auí AUI CO., LTD

4F, Tolin Bldg,
16-19 Nihombashi Kodemma-cho,
Chuo-ku, Tokyo
103-0001 JAPAN
Tel : +81-3-5640-1121
Fax : +81-3-6231-1518
URL : <http://www.aui.co.jp>
E-mail : pr-aui@au.co.jp